

**n-Butyl acetate**

## • General grade

| Range(cmol/mol) |        |        | Cylinder type | Blending tolerance(%) | Uncertainty (%) | Shelf life (months) | Pressure  |        |
|-----------------|--------|--------|---------------|-----------------------|-----------------|---------------------|-----------|--------|
|                 |        |        |               |                       |                 |                     | psig      | MPa    |
| 1               | 0.0001 | 0.0003 | Al-B          | 10                    | 5               | 6                   | 1500      | 10     |
| 2               | 0.0003 | 0.0006 | Al-B          | 10                    | 3               | 6                   | 1500      | 10     |
| 3               | 0.0006 | 0.0022 | Al-B          | 5                     | 3               | 12                  | 1500      | 10     |
| 4               | 0.0022 | 0.0055 | Al-A          | 5                     | 2               | 12                  | 1500      | 10     |
|                 |        |        | Al-B          | 5                     | 2               | 12                  | 1500      | 10     |
| 5               | 0.0055 | 0.011  | Al-A          | 3                     | 2               | 12                  | 1300~1500 | 8.5~10 |
|                 |        |        | Al-B          | 3                     | 2               | 12                  | 1300~1500 | 8.5~10 |
| 6               | 0.011  | 0.11   | Al-A          | 2                     | 2               | 12                  | 150~1300  | 1~8.5  |
|                 |        |        | Al-B          | 2                     | 2               | 12                  | 150~1300  | 1~8.5  |
| 7               | 0.11   | 100    | Steel-A       | 2                     | 2               | 12                  | 0~150     | 0~1    |
|                 |        |        | Steel-B       | 2                     | 2               | 12                  | 0~150     | 0~1    |
|                 |        |        | Al-A          | 2                     | 2               | 12                  | 0~150     | 0~1    |
|                 |        |        | Al-B          | 2                     | 2               | 12                  | 0~150     | 0~1    |

## • Special grade

| Range(cmol/mol) |  |  | Cylinder type | Blending tolerance(%) | Uncertainty (%) | Shelf life (months) | Pressure |     |
|-----------------|--|--|---------------|-----------------------|-----------------|---------------------|----------|-----|
|                 |  |  |               |                       |                 |                     | psig     | MPa |
|                 |  |  |               |                       |                 |                     |          |     |
|                 |  |  |               |                       |                 |                     |          |     |
|                 |  |  |               |                       |                 |                     |          |     |
|                 |  |  |               |                       |                 |                     |          |     |

## • Equipment recommendations

| Regulator Model* |            | GB | GS | SB | SS |
|------------------|------------|----|----|----|----|
| Concentration    | ~0.0005    | △  | △  | ○  | ○  |
| Range (cmol/mol) | 0.0005~0.5 | ○  | ○  | ○  | ○  |
|                  | 0.5~       | ○  | ○  | ○  | ○  |

O: Available, △: Available but not recommended, X: N/A(not available)

\* GB : G-series Brass Regulator

GS : G-series SUS Regulator

SB : S-series Brass Regulator

SS : S-series SUS Regulator

RIGAS Co., Ltd manufactures various specifications of gas and liquid standard materials.

- Atmospheric environmental gas, Automobile exhaust gas, Petrochemical and Natural Gas

- Laser gas mixtures, Odor standards, Volatile organic compound standards (VOCs)